

W2

Electric Friends Tower is the obvious camera carrier on top of the Electric Friends Trolley, providing:

- panning, elevation and tilt
- zoom and focus lens control
- prompter and program monitor
- decorative form, with trim adaptable to studio design
- talley light, on air and preview

Key features:

- Linear elevation actuator
- Heavy duty panorate bearing secures stable tower and low center of gravity
- Actuators with exceptional accuracy and repeatability
- Built-in absolute encoders provides accurate coordinates for AR and VR systems.
- Easy set up and calibration
- Homogeneous circular surface avoids people security hazard during movements
- Small camera glassed-in version as well a box-camera lens cut-out version
- Textile or hard surface choices and varieties of colors

Technical Data:

- Pan Angle +/- 270
- Pan Speed 55 °/s
- Tracking accuracy 0.1 mm
- Camera Elevation height span 0.8 - 1.9 m
- Tracking update frequency 50 Hz
- Camera Elevation speed 0.2 m/s
- Idle power consumption 95 W
- Tilt Angle +/- 18°
- Tilt Speed 14 °/s

Tower	Camera System		Outside trim	
W2	P1	Box camera Sony P1, GV LDX 80 or similar	Molded felt	Antrasitt Black White Red Blue Other colors on request
W2	DSLR1	Multi-purpose camera Canon ME200S-SH or similar	RFI	Please request your choice of hard trim, color or wallpaper

Data subject to change without notice. Please consult relevant documents at time of purchase.